

<b><u>Startup Checklist</u></b>		<b><u>Check</u></b>
1	GLV Battery is connected to the J1 2 pin DT connector	
2	Twist open right side BRB	
3	Twist open left side BRB	
4	Turn on GLVMS on right side panel	
5	Check GLV light is on	
6	Check IMD light is on then goes off	
7	Check Fault light is on then goes off with IMD	
8	Check Current/Voltage and Power Display on GLV Box is on	
9	Check VSCADA Display on GLV Box is on	
10	Cooling System Flow Rate ~6L/S	
11	Driver start recording, log driver name, secession number	
12	Press green Mreset button on right side panel	
13	Check Safe light is on	
14	Assure that driver is conscious and ready	
15	Make sure no one is in front of or behind the car	
16	Driver should twist open cockpit BRB.	
17	Driver should press green Mreset on cockpit panel	
18	Turn on TSVMS on right side panel (observe that AIRs LED is lit)	
19	Check AIRs light is on	
20	Check TSEL light is on	
21	Driver should press brake, and not accelerator, and press drive button	
22	Check Drive light on	
23	Drive	

<b><u>Shutdown Checklist</u></b>		<b><u>Check</u></b>
1	Press Drive button, exist drive mode	
2	Drive LED is off	
3	Press Cocckpit BRB	
4	HV LED is off	
5	TSEL is off	
6	Press stop record on the driver display	