

PacMAN Programming User Manual

Pack Management System

Last Updated 4/13/2017, Marty Townley

Originally Written 12/19/15, John Gehrig

Overview

This document describes the methods and procedures to build and upload code to the Rev 0.3 and later PACMAN boards.

Prerequisites


You will need the following programs installed on the development machine. The procedure is designed for a Linux environment; the Oracle VM VirtualBox on the computer in the safety zone room 400 is useful for installation as all the necessary programs are installed.

- Oracle VM VirtualBox Information:
 - Username: “osboxes”
 - Password: “password”
 - Root Password: “password”
- AVR-GCC (<http://www.nongnu.org/avr-libc/>)
(For details see http://avr-eclipse.sourceforge.net/wiki/index.php/The_AVR_GCC_Toolchain)
- GNU Make (<https://www.gnu.org/software/make/>)
- AVRDUDE (<http://www.nongnu.org/avrdude/>)
- Atmel ICE Basic Programmer




Software Build Procedure


All source code is located in the 'software' folder of the PacMAN repository; this has been uploaded to the 2017 website in a PacMAN software zip folder (<https://sites.lafayette.edu/ece492-sp17/subsystems/tsv/pacman/>).



Navigate to the folder containing 'Makefile'



Open a terminal and type make



Here is an example of

“good” make output

```
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/main.c -o build/main.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/i2c.c -o build/i2c.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/task_gui.c -o build/task_gui.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/task_watchdog.c -o build/task_watchdog.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/task_control.c -o build/task_control.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/task_safety.c -o build/task_safety.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/task_config.c -o build/task_config.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/task_canbus.c -o build/task_canbus.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib src/tasklist.c -o build/tasklist.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -x assembler-with-cpp -Isrc -Ikernel kernel/atomport-asm.s -o
build/atomport-asm.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -I. -Isrc kernel/atomkernel.c -o build/atomkernel.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -I. -Isrc kernel/atomsem.c -o build/atomsem.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -I. -Isrc kernel/atommutex.c -o build/atommutex.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -I. -Isrc kernel/atomtimer.c -o build/atomtimer.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -I. -Isrc kernel/atomqueue.c -o build/atomqueue.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -I. -Isrc kernel/atomport.c -o build/atomport.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib lib/uart/uart.c -o build/uart.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib lib/atmel/TWI_Master.c -o build/TWI_Master.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib lib/atmel/can_drv.c -o build/can_drv.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib lib/atmel/can_lib.c -o build/can_lib.o
avr-gcc -c -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 -Isrc -Ikernel -Ilib lib/lcd/lcd.c -o build/lcd.o
#avr-gcc -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 build/main.o build/main.o build/i2c.o build/task_gui.o build/task_watchdog.o
build/task_control.o build/task_safety.o build/task_config.o build/task_canbus.o build/tasklist.o build/atomport-asm.o
build/atomkernel.o build/atomsem.o build/atommutex.o build/atomtimer.o build/atomqueue.o build/atomport.o build/uart.o
build/TWI_Master.o build/can_drv.o build/can_lib.o build/lcd.o -o build/pacman.elf -Wl,-Map,build/pacman.map
echo build/main.o build/i2c.o build/task_gui.o build/task_watchdog.o build/task_control.o build/task_safety.o build/task_config.o
build/task_canbus.o build/tasklist.o build/atomport-asm.o build/atomkernel.o build/atomsem.o build/atommutex.o build/atomtimer.o
build/atomqueue.o build/atomport.o build/uart.o build/TWI_Master.o build/can_drv.o build/can_lib.o build/lcd.o
build/main.o build/i2c.o build/task_gui.o build/task_watchdog.o build/task_control.o build/task_safety.o build/task_config.o
build/task_canbus.o build/tasklist.o build/atomport-asm.o build/atomkernel.o build/atomsem.o build/atommutex.o build/atomtimer.o
build/atomqueue.o build/atomport.o build/uart.o build/TWI_Master.o build/can_drv.o build/can_lib.o build/lcd.o
avr-gcc -g -O3 -mmcu=at90can32 -Wall -Werror -std=c99 build/main.o build/i2c.o build/task_gui.o build/task_watchdog.o
build/task_control.o build/task_safety.o build/task_config.o build/task_canbus.o build/tasklist.o build/atomport-asm.o
build/atomkernel.o build/atomsem.o build/atommutex.o build/atomtimer.o build/atomqueue.o build/atomport.o build/uart.o
build/TWI_Master.o build/can_drv.o build/can_lib.o build/lcd.o -o build/pacman.elf -Wl,-Map,build/pacman.map
Building pacman.hex
avr-objcopy -j .text -j .data -O ihex build/pacman.elf build/pacman.hex
avr-size -C --mcu=at90can32 build/pacman.elf
AVR Memory Usage
-----
Device: at90can32
Program: 11636 bytes (35.5% Full)
(.text + .data + .bootloader)
Data: 994 bytes (48.5% Full)
(.data + .bss + .noinit)
```

Make will output a file in the build directory based on the variable 'TARGET_NAME'. The default output is to build/pacman.hex. This file can be manually uploaded through avrdude, or automatically from make.

NOTE: Device resource usage is listed at the bottom of the make file.

After this completes, run `sudo make fuse` command; this will set the lower byte of the fusing outputs to set the clock speed. If this command is not run, the PacMAN will run off the internal clock instead of the external oscillator. This is an example of a good output for this command:

```
osboxes@osboxes:~/Desktop/Pacman_Software_0_15_Emilie_Marty/Software$ sudo make fuse
#see http://www.engbedded.com/fusecalc/ for details on what these settings do
avrdude -F -V -c atmelice -p c128 -U lfuse:w:0xcff:m -U hfuse:w:0x99:m -U efuse:w:0xff:m

avrdude: AVR device initialized and ready to accept instructions

Reading | ##### | 100% 0.09s

avrdude: Device signature = 0x1e9781 (probably c128)
avrdude: reading input file "0xcff"
```

```
avrdude: writing lfuse (1 bytes):
Writing | ##### | 100% 0.01s
avrdude: 1 bytes of lfuse written
avrdude: reading input file "0x99"
avrdude: writing hfuse (1 bytes):
Writing | ##### | 100% 0.01s
avrdude: 1 bytes of hfuse written
avrdude: reading input file "0xff"
avrdude: writing efuse (1 bytes):
Writing | ##### | 100% 0.01s
avrdude: 1 bytes of efuse written
avrdude: safemode: Fuses OK (E:FF, H:99, L:CF)
avrdude done. Thank you.
```

NOTE: The current makefile is set such that when programming, the EEPROM is preserved. To enable resetting the EEPROM while the Pacman is being programmed, change the fuse setting in the Makefile from:

```
lfuse:w:0xcf:m -U hfuse:w:0x91:m -U efuse:w:0xff:m
```

to

```
lfuse:w:0xcf:m -U hfuse:w:0x99:m -U efuse:w:0xff:m
```

Adding Files to the Project

SRC_DIR – Directory containing all source files.

LIB_DIR – Directory containing all library files.

BUILD_DIR – The directory to which program output should be directed.

APP_OBJECTS – A list of individual source files, must have a .o extension

LIB_OBJECTS – A list of library source files, must have a .o extension

To add a file to the project, you must first determine if it should be treated as a library, or as a source file. Library files should be added to the LIB_OBJECTS variable with the .c extension replaced with .o, folder path should be included. Source files should be added to the APP_OBJECTS variable, no folder path is required, but the extension should also be converted from .c to .o.

For example, to add the source file src/foo.c to the project, the following code would be added to the make file.


```
APP_OBJECTS = {all other source files} foo.o
```

A library file named baz/bar.c would be added as follows

```
LIB_OBJECTS = {all other source files} baz/bar.o
```

Programming the Target Device

Ensure the Atmel ICE device is attached to your computer. If you are using a virtual machine, ensure a filter rule is present so the device can be recognized by the guest machine.



Place the JTAG connector in the AVR receptacle on the Atmel ICE



Attach the provided cable to the JTAG port of the PACMAN target board.



Open a terminal and type the following command (`sudo make program`):

```
File Edit View Bookmarks Settings Help
lifebookt732 software # make program
software : bash
```

NOTE: You will have to run this command as root!

Here is successful programming output:

```
lifebookt732 software # make program
avr-size -C build/pacman.hex
AVR Memory Usage
-----
Device: Unknown
Program:      0 bytes
(.text + .data + .bootloader)

Data:         0 bytes
(.data + .bss + .noinit)

avrdude -F -V -c atmelice -p c32 -U flash:w:build/pacman.hex
avrdude: usbdev_open(): WARNING: failed to set configuration 1: Device or resource busy
avrdude: AVR device initialized and ready to accept instructions
Reading | ##### | 100% 0.07s
avrdude: Device signature = 0x1e9581
avrdude: NOTE: "flash" memory has been specified, an erase cycle will be performed
        To disable this feature, specify the -D option.
```

```
avrdude: erasing chip
avrdude: reading input file "build/pacman.hex"
avrdude: input file build/pacman.hex auto detected as Intel Hex
avrdude: writing flash (11636 bytes):
Writing | ##### | 100% 1.13s
avrdude: 11636 bytes of flash written
avrdude: safemode: Fuses OK (E:FF, H:99, L:CF)
avrdude done. Thank you.
```

Note: Verify that the second to last line describing the Fuses OK indicates that L : CF. If the `make fuses` command was run successfully, then this should be the case. If not, run the `make fuses` command.