

<u>Startup Checklist</u>		<u>Check</u>
1	GLV Battery is connected to the J1 2 pin DT connector	
2	Twist open right side BRB	
3	Twist open left side BRB	
4	Turn on GLVMS on right side panel	
5	Check GLV light is on	
6	Check IMD light is on then goes off	
7	Check Fault light is on then goes off with IMD	
8	Check Current/Voltage and Power Display on GLV Box is on	
9	Check VSCADA Display on GLV Box is on	
10	Cooling System Flow Rate ~6L/S	
11	Press green Mreset button on right side panel	
12	Check Safe light is on	
13	Assure that driver is conscious and ready	
14	Make sure no one is in front of or behind the car	
15	Driver should twist open cockpit BRB.	
16	Driver should press green Mreset on cockpit panel	
17	Turn on TSVMS on right side panel (observe that AIRs LED is lit)	
18	Check AIRs light is on	
19	Check TSEL light is on	
20	Driver should press brake, and not accelerator, and press drive button	
21	Check Drive light on	
22	Drive	

<u>Shutdown Checklist</u>		<u>Check</u>
1	Press Drive button, exist drive mode	
2	Drive LED is off	
3	Press Cocckpit BRB	
4	HV LED is off	
5	TSEL is off	